

BLANK PAGE



Indian Standard SPECIFICATION FOR HANDLOOM COTTON CREPE

(First Revision)

UDC 677.21.064.67



© Copyright 1978

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard

SPECIFICATION FOR HANDLOOM COTTON CREPE

(First Revision)

Handloom and Khadi Sectional Committee, TDC 13

Chairman

Representing

DIRECTOR OF HANDLOOMS AND Directorate of Handlooms & Textiles, Government
TEXTILES of Tamil Nadu, Madras

Members

JOINT DIRECTOR OF HANDLOOMS
AND TEXTILES (Alternate to
Director of Handlooms and
Textiles)

SHRI B. P. AGARWAL Government of Uttar Pradesh SHRI G. D. BANERJEE (Alternate)

SHRI P. C. AGARWAL Ministry of Defence (R & D)

SHRI K. NAGARAJAN (Alternate)

Shri A. T. Basak Inspection Wing, Directorate General of Supplies & Disposals, New Delhi

SHRI A. R. HALDAR (Alternate)
CHIEF EXECUTIVE OFFICER

Maharashtra State Khadi & Village Industries
Board, Bombay

DEPUTY EXECUTIVE OFFICER
(DEVELOPMENT) (Alternate)

Textiles Committee, Bombay

CHIEF INSPECTING OFFICER
DEPUTY CHIEF INSPECTING

ER (Alternate)
SH DAS Directorate of Industries, Government of West

OFFICER (Alternate)
SHRI PARITOSH DAS

Bengal, Calcutta

Shri P. K. Das (Alternate) Shri J. S. Grewal

Directorate of Industries, Government of Punjab, Chandigarh

SHRI MOHINDER SINGH (Alternate)
SHRI D. S. V. IYER All II

All India Handloom Board, Bombay

Shri K. Manivannan

Directorate of Industries, Government of Haryana, Chandigarh

SHRI C. R. YADAV (Alternate) MAJ J. S. NEHRA

Ministry of Defence (DGI)

SHRI S. S. ROBINSON (Alternate)

(Continued on page 2)

© Copyright 1978

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 1100 - 1978

(Continued from page 1)

Members

Representing

SHRI RAMU BHAI PATEL

PRINCIPAL, INDIAN INSTITUTE OF HANDLOOM TECHNOLOGY,

VARANASI SHRI T. RANGASWAMY

REGIONAL MANAGER

SECRETARY

SHRI A. RAJAMANI (Alternate) SENIOR EXECUTIVE AND SPECIAL OFFICER

PRODUCT DEVELOPMENT MANAGER (Alternate) SHRI P. VENKATARAMAN

SHRI S. M. CHAKRABORTY, Director (Tex)

Gujarat Rajya Khadi Gramodyog Board, Ahmadabad All India Handloom Board, Bombay

Southern India Millowners' Association, Coimba-

Andhra Pradesh Handloom Weavers' Co-operative

Society Ltd, Vijaywada All India Handloom Fabrics Marketing Co-operative Society Ltd, Bombay

Tamil Nadu Handloom Weavers' Co-operative Society Ltd. Madras

Export Inspection Council of India, New Delhi Director General, ISI (Ex-officio Member)

Secretary

SHRI O. P. KHULLAR Deputy Director (Tex), ISI

Handloom and Khadi Cotton Cloth Subcommittee, TDC 13:1

Convener

PRINCIPAL, INDIAN INSTITUTE OF All India Handloom Board, Bombay HANDLOOM TECHNOLOGY. VARANASI

Members

SHRI B. P. AGARWAL

Government of Uttar Pradesh SHRI G. D. BANERJEE (Alternate)

Inspection Wing, Directorate General of Supplies & SHRI A. T. BASAK

Disposals, New Delhi

SHRI A. R. HALDAR (Alternate)

Directorate of Industries, Government of Punjab. SHRI I. S. GREWAL Chandigarh

SHRI MOHINDER SINGH (Alternate)

SHRI B. R. KOWSHIK

Maj J. S. Nehra

Textiles Committee, Bombay Ministry of Defence (DGI)

SHRI S. S. ROBINSON (Alternate)

Khadi & Village Industries Commission, Bombay SHRI C. V. PRABHAKARAN SHRI T. GOVINDAN NAIR (Alternate)

PRINCIPAL, INDIAN INSTITUTE OF All India Handloom Board, Bombay HANDLOOM TECHNOLOGY,

SALEM

SHRI S. RANGARAJAN

The Handicrafts & Handlooms Exports Corporation of India Ltd, Madras

Tamil Nadu Handloom Weavers' Co-operative SENIOR EXECUTIVE AND SPECIAL Society Ltd. Madras OFFICER

PRODUCT DEVELOPMENT MANAGER (Alternate)

SHRI T. O. THOMAS

Kerala State Handloom Weavers' Co-operative Society Ltd, Trivandrum

SHRI R. VIJAYAPPAN NAIR (Alternate)

Indian Standard SPECIFICATION FOR HANDLOOM COTTON CREPE

(First Revision)

0. FOREWORD

- **0.1** This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 5 June 1978, after the draft finalized by the Handloom and Khadi Sectional Committee had been approved by the Textile Division Council.
- 0.2 This standard which was first published in 1957 has been revised to make it up to date. The constructional particulars of such varieties of crepe cloth, which are in vogue, have been incorporated. Other important changes carried out in the standard are:
 - a) deletion of breaking strength values, and
 - b) inclusion of inspection, marking and packing clauses.
- 0.3 The cloth covered by this standard is woven in plain weave with high twisted cotton yarn having twist multiplier around 8.25. The twist in warp and west yarn shall be in the same direction. The cloth develops the crepe effect on processing it in caustic soda.
- 0.4 To familiarize the industry with International System of Units (SI Units), the basic SI Units as well as the recommended SI Units for use in the textile industry are given in Appendix B.
- 0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

^{*}Rules for rounding off numerical values (revised).

IS: 1100 - 1978

1. SCOPE

- 1.1 This standard prescribes the constructional particulars and other requirements of three varieties of handloom cotton crepe, bleached, dyed, printed, striped or checked.
- 1.2 This standard does not specify the general appearance, feel, shade, finish, etc, of the cloth (see also 3.3).

2. MANUFACTURE

- 2.1 Yarn The cotton yarn used in the manufacture of crepe shall be satisfactory in evenness and reasonably free from neps and spinning defects. The yarn shall be highly twisted having twist multiplier of around 8.25.
- 2.2 Cloth The cloth shall be woven in plain weave and shall be free from dressing and filling materials and from substances liable to cause subsequent tendering.

3. REQUIREMENTS

- 3.1 The constructional particulars of cloth shall conform to those given in Table 1. The loomstate particulars, that is, ends and picks in the loomstate are also given in the table.
- 3.2 The colour fastness ratings and other requirements of the cloth shall conform to those given in Table 2.
- 3.3 If in order to illustrate or specify the indeterminable characteristics, such as general appearance, lustre, feel and shade of the cloth, a sample has been agreed upon and sealed, the supply shall be in conformity with the sample in such respects.
- 3.3.1 The custody of the sealed sample shall be a matter of prior agreement between the buyer and the seller.

4. INSPECTION

- 4.1 The cloth when visually inspected shall be reasonably free from the following defects:
 - a) West crack of more than two missing picks across the width of the material;
 - b) Prominently noticeable weft bar due to the difference in raw material, count, twist, lustre, colour, shade or pick spacing of adjacent groups of weft yarn;

- c) More than two adjacent ends running parallel, broken or missing and extending beyond 15 cm;
- d) Prominent selvedge defects;
- e) Noticeable warp or west float;
- f) Noticeable oil or other stains;
- g) Noticeable hole, cut or tear up to 3 mm in size;
- h) Smash rupturing the texture of the fabric; and
- j) Prominently noticeable printing or dyeing defect.
- 4.1.1 A reference may be made to IS: 4125-1967* for details of these defects.

5. MARKING

- 5.1 Each piece shall be suitably marked or labelled with the following information:
 - a) Name of the material;
 - b) Manufacturer's name, initials or trade mark;
 - c) Length and width of the piece; and
 - d) Count of warp and weft yarn.
 - 5.1.1 The cloth may also be marked with the ISI Certification Mark.

Note — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

6. PACKING

6.1 Unless otherwise agreed upon the buyer and the seller, the cloth shall preferably be packed in bales or cases in conformity with the procedure laid down either in IS: 1347-1972† or IS: 293-1967‡.

7. SAMPLING

7.1 Lot — The quantity of handloom crape of the same width and colour delivered to a buyer against a despatch note shall constitute a lot.

^{*}Glossary of terms pertaining to defects in fabrics.

[†]Specification for inland packaging of cotton cloth and yarn (first revision).

[#]Specification for seaworthy packaging of cotton cloth and yarn (second revision).

TABLE 1 CONSTRUCTIONAL PARTICULARS OF HANDLOOM COTTON CREPE (Clause 3,1)

VARI-	COUNT OF		Processi	ED CLOTH	LOOMSTAT	е Ссотн	LENGTH	Width
No.	Warp	Weft	Ends/	Picks/	Ends/	Picks/		
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
1	20s (30 tex)	20s (30 tex)	16	18	15	17	m 40	cm 71, 102
2	40s (14.5 tex)	40s (14.5 tex)	24	29	23	· 2 7	or as agreed	or as agreed
3	60s (10 tex)	60s (10 tex)	34	29	32	27		
Toler- ance, Per- cent	. ±5	± 5	± 5	± 5	± 5	± 5		± 2
METHO OF TE	on IS:3442-1966* sr	IS: 3442-1966*	IS: 1963- 1969†	IS : 1963- 1969†	IS : 1963- 1969†	IS: 1963- 1969†	IS: 1954- 1969‡	IS: 1954- 1969‡

NOTE — In case of crepe fabrics woven in rib, check or stripes, the number of ends and picks may vary due to the use of coarse yarn alongwith high twisted yarn.

9

^{*}Method for determination of crimp and count of yarn removed from fabrics.

[†]Methods for determination of threads per decimetre in woven fabrics (first revision).

†Methods for determination of length and width of fabrics (first revision).

TABLE 2 REQUIREMENTS OF HANDLOOM COTTON CREPE
(Clause 3.2)

St No.	CHARACTERISTIC	REQUIREMENT	Method of Test, Ref to
(1)	(2)	(3)	(4)
i)	Colour fastness to:		
	a) Light	5 or better	IS: 686-1957* or IS: 2454-1967†
	b) Washing: Test 3	4 or better	IS: 764-1966‡
ii)	Dimensional change, percent, Max	4.0	IS: 2977-1969§
iii)	Scouring loss, percent, Max	2.5	IS: 1383-1977
iv)	pH value of aqueous extract	6·0 to 8·5	Appendix A

*Method for determination of colour fastness of textile materials to daylight.

†Method for determination of colour fastness of textile materials to artifical light (xenon lamp).

#Method for determination of colour fastness of textile materials to washing: Test 3

(revisea).

§Method for determination of dimensional changes of woven fabrics (other than wool) on soaking in water.

||Method for determination of scouring loss in grey and finished cotton textile materials (first revision).

7.2 To ascertain the conformity of the lot to the requirements of this standard, samples shall be drawn and inspected from each lot separately.

7.3 The number of pieces to be selected at random for inspection shall be in accordance with Table 3.

TABLE 3 SAMPLE SIZE AND PERMISSIBLE NUMBER OF NON-CONFORMING PIECES

LOT SIZE	Sample Size	Permissible Number of Non-conforming Pieces	Sub-sample Size
(1)	(2)	(3)	(4)
Up to 25	3	0	2
26 ,, 50	5	0	2
51 ,, 150	8	0	3
151 ,, 300	13	1	3
301 ,, 500	20	1	5
501 and above	32	2	8

7.4 Number of Tests and Criteria for Conformity

Characteristics	Number of Tests	Criteria for Conformity
Visual inspection, ends, picks, length and width	According to col 2 of Table 3	Number of non-conforming pieces not to exceed corresponding number given in col 3 of Table 3
Count of yarn, colour fastness to washing, dimensional change, scouring loss and pH value	According to col 4 of Table 3	All the test specimens to meet the corresponding requirements
Colour fastness to light	2 for lot size of 300 or less and 3 other- wise	do

APPENDIX A

(Table 2)

METHOD FOR DETERMINATION OF pH VALUE OF AQUEOUS EXTRACT

- A-1. APPARATUS
- A-1.1 Erlenmeyer Flask
- A-1.2 Reflux Condenser
- A-2. REAGENTS
- A-2.1 Distilled Water See IS: 1070-1977*.
- A-2.2 Indicator pH Papers

^{*}Specification for water for general laboratory use (second revision).

A-3. PROCEDURE

- A-3.1 Draw from each piece in the test sample at least two test specimens and cut it into small bits. Put the bits in the Erlenmeyer flask and add to this 50 ml of distilled water. Boil the contents for one hour under the reflux condenser. Stopper the flask and cool the contents. Decant the supernatant extract in a test tube.
- **A-3.2** Take the pH indicator paper. Dip it in the extract and compare the colour of the moistened indicator paper with those printed on the booklet or dispenser containing the indicator paper. Designate the number written on a particular colour shade with which the moistened indicator paper matches as pH of the extract.

A-3.3 Similarly, test the remaining test specimen(s).

A-4. REPORT

A-4.1 Report the pH value of the extract as determined above.

APPENDIX B

(Clause 0.4)

SI UNITS

TABLE 4 INTERNATIONAL SYSTEM OF UNITS

QUANTITY	Unit	Symbol
Length	metre	m
Mass	kilogram	kg
Time	second	5
Electric current	ampere	Α
Thermodynamic temperature	kelvin	K
Luminous intensity	candela	cd
Amount of substance	mole	mol
Supplementary Units		

QUANTITY	Unit	Symbol
Plane angle	radian	rad
Solid angle	steradian	sr

Derived Units

QUANTITY	Unit	Ѕумвот.	Conversion
Force	newton	N	1 N = 0.101 972 kgf
Energy	joule	\mathbf{J}°	1 J = 1 N.m
Power	watt	W	1 W = 1 J/s
Flux	weber	Wb	1 Wb = 1 V.s
Flux density	tesla	T	$1 T = 1 \text{ Wb/m}^2$
Frequency	hertz	Hz	$1 \text{ Hz} = 1 \text{ c/s } (s^{-1})$
Electric conductance	siemens	S	1 S = 1 A/V
Pressure, stress	pascal	Pa	$1 Pa = N/m^2$

	TABLE 5	RECOMMENDED SI	UNITS F	OR TEXTILES
SL No.	CHARACTERIST	O SI Unite	3	Application
NO.		Unit A	bbreviation)
(1)	(2)	(3)	(4)	(5)
1.	Length	Millimetre Millimetre, centimetre Metre	mm mm, cm m	Fibre Samples and test specimens (as appropriate) Yarns, ropes and cordages, fabrics
2.	Width	Millimetre Centimetre Millimetre, centimetre Centimetre, metre	mm cm mm, cm cm, m	Narrow fabrics Other fabrics Samples and test specimen (as appropriate) Carpets, druggets, DURRIES (as appropriate)
3.	Thickness	Micrometre	μm	Delicate fabrics
		(micron) Millimetre	mm	Other fabrics, carpets, felts
4.	Linear density	Tex Millitex Decitex	tex mtex dtex	Yarns Fibres Filament and filament yarns
_	D.	Kilotex	ktex	Slivers, ropes and cordages
5,	Diameter	Micrometre (micron) Millimetre	μm mm	Fibres Yarns, ropes, cordages
6. 7.	Circumference Threads in cloth:	Millimetre	mm	Ropes, cordages Woven fabrics (as appropriate)
	a) Length	Number per centimetre Number per	ends/cm ends/dm	appropriate j
	b) Width	decimetre Number per	picks/cm	
		centimetre Number per decimetre	picks/dm	
8.	Warp threads in	Number per centimetre	ends/cm	Reeds
9,	Stitches in knitted	ì		Knitted fabrics (as appropriate)
	a) Length	Courses per centimetre Courses per decimetre	courses/dm	
	b) Width	Wales per centimetre	wales/cm	
		Wales per decimetre	wales/dm	
				(Continued)

TABLE 5 RECOMMENDED SI UNITS FOR TEXTILES - Contd

SL	Characteristic	SI Units		Application
No.		Unit A	bbreviation	1
(1)	(2)	(3)	(4)	(5)
10.	Stitch length	Millimetre	mm	Knitted fabrics Made-up fabrics
11.	Mass per unit area	Grams per square metre	g/m³	Fabrics
12.	Mass per unit length	Grams per metre	g/m	Fabrics
13.	Twist	Turns per centi- metre Turns per metre	turns/cm turns/m	Yarns, ropes (as appropriate)
14.	Test or gauge length	Millimetre, centi- metre	mm, cm	Fibres, yarns and fabric specimens (as appropriate)
15.	Breaking load	Millinewton	mN	Fibres, delicate yarns
		Newton .	N	(skeins or individual) Strong yarns (individual or skeins), ropes and cordages, fabrics
16.	Breaking length	Kilometre	km	Yarns
17.	Tenacity	Millinewton per tex	mN/tex	Fibres, yarns (individual or skeins)
18.	Twist factor or twist multiplier	Turns per centi- metre × square root of tex	turns/cm × 1/tex	Yarns (as appropriate)
		Turns per metre × square root of tex	turns/m × 1/tex	
19.	Bursting strength	Newton per square centi- metre	N/cm²	Fabrics
20.	Tear strength	Millinewton	mN	Fabrics (as appropriate)
		Newton	N.	
21.	Pile height	Millimetre	mm	Carpets
	Pile density	Mass of pile yarn in grams per square metre per millimetre pile height	g/m²/mm p i l e height	Pile carpet
23.	Elastic modulus	Millinewton per tex per unit deformation	mN/tex/ unit deform- ation	Fibres, yarns, strands

PUBLICATIONS OF INDIAN STANDARDS INSTITUTION

INDIAN STANDARDS

Over 9 000 Indian Standards covering various subjects have been issued so far. Of these, the standards belonging to the Textile Group fall under the following categories:

Aeronautical textiles
Chemical test methods
Colour fastness of textile
materials
Cotton fabrics — handloom, khadl,
and mill-made
Dyestuffs
Grading of fibres and yarns
Grading of raw silk
Hosiery
Jute — bags and fabrics
Jute mill accessories
Narrow fabrics
National flag of India
Nylon fabrics
Packaging code
Physical test methods
Rayon fabrics
OTHER RUDI

Hantex Bldg (2nd Floor), Rly Station Road

Rayon fabrics, handloom Ropes and cordages Sampling of textiles, methods for Silk fabrics - handloom and khadi Sizing and finishing materials Spinning machinery components Terminology Textile floor coverings Textile materials for fishing Textile mill accessories (other than jute mills) Twines Weaving machinery components Wool fabrics - handloom, khadl, and mill-made Yarn and similar structures Unclassified

OTHER PUBLICATIONS

ISI Bulletin (Published Every N	Month)				
Single Copy					Rs 4.00
Annual Subscription					Rs 36.00
Standards: Monthly Additions					
Single Copy	***				Re 0.30
Annual Subscription					Rs 3.00
Annual Reports (from 1948-49	Onwards)	1		Rs	2.00 to 7.00
ISI Handbook, 1975			`		Rs 30.00

INDIAN STANDARDS INSTITUTION

III DIAIL C. III -		
Manak Bhavan, 9 Bahadur Shah Zafar	Marg, NEW DELHI 110002	
Telephone: 27 01 31 (20 lines)	Telegrams: Manaksanstha	
Regional Offices:	Telephone	
Western: Novelty Chambers, Grant Road Eastern: 5 Chowringhee Approach Southern: C.I.T. Campus, Adyar	BOMBAY 400007 37 97 29 CALCUTTA 700072 23-08 02 MADRAS 600020 41 24 42	
Branch Offices:		
'Pushpak' Nurmohamed Shaikh Marg, Khanpur, F' Block, Unity Bldg, Narasimharaja Square R-26, Guru Teg Bahadur Complex Showhouse Bldg, Sachivalaya Marg Ahimsa Bldg, SCO 82-83, Sector 17C 5-8-56/57 L. N. Gupta Marg D-277 Todarmal Marg, Banipark 117/418 B Sarvodaya Nagar	AHMADABAD 380001 2 76 49 BANGALORE 560002 6 27 16 BHUBANESHWAR 751001 5 36 27 CHANDIGARH 160017 2 83 20 HYDERABAD 500001 22 10 83 JAIPUR 302006 6 98 32 KANPUR 208005 82 72	
B.C.I. Bldg (3rd Floor), Gandhi Maidan East	PATNA 800004 5 36 55	

TRIVANDRUM 695001